

# MATERIAL SAFETY DATA SHEET

## BLACK STOVE PAINT

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

**1.1 Product identifier** For Industrial, professional and consumer only

**Trade name:** Symphony Narrowboat Paint Black Stove Paint

**1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating

**Relevant uses:** Surface Coating. Synthetic Topcoat  
**Uses advised against:** All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet**

**Supplier:** SYMPHONY COATINGS GROUP LTD  
10A GRANGE WAY  
WHITEHALL IND EST  
COLCHESTER  
CO2 8HG  
UNITED KINGDOM  
Tel: 03333208821  
Email: [hs@symphonynarrowboatpaint.co.uk](mailto:hs@symphonynarrowboatpaint.co.uk)

**Further information from:** [hello@symphonynarrowboatpaint.co.uk](mailto:hello@symphonynarrowboatpaint.co.uk)

**1.4 Emergency number** 03333208821 (business hours)

### SECTION 2: Hazards identification

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226 Flammable liquid and vapour
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H336 May cause drowsiness or dizziness.
STOT RE 1	H372 Causes damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3	H411 Toxic to aquatic life with long lasting effects.

**2.2 Label elements**

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms:**



**Signal word:** Danger

**Hazard-determining components of labelling:** Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)  
4-isopropenyl-1-methylcyclohexane

**Hazard statements:** phthalic anhydride  
2-butanone oxime  
cobalt bis(2-ethylhexanoate)  
H226 Flammable liquid and vapour  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements:** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

**Results of PBT and vPvB assessment:** PBT: Not applicable.  
vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

**3.1 Substance:** Non-applicable

**3.2 Mixture:** Mixture of substances listed below with non-hazardous additions.

### Dangerous components:

EC number: 919-446-0 Reg.nr.: 01-2119458049-33-xxxx	Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	>25 - <50%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	>10 - <25%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light aromatic Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	>2.5 - <10%
CAS: 138-86-3 EINECS: 205-341-0 Reg.nr.: 01-2120766421-57-0000	4-isopropenyl-1-methylcyclohexane Flam. Liq. 3, H226; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317	>1 - <2.5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	Xylene (mix) Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	>1 - <2.5%
CAS: 96-29-7 EINECS: 202-496-6 Reg.nr.: 01-2119539477-28	2-butanone oxime Carc. 2, H351; Eye Dam. 1, H318; Acute Tox. 4, H312; Skin Sens. 1, H317	<1%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	cobalt bis(2-ethylhexanoate) Repr. 1B, H360F; Aquatic Acute 1, H400; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	<1%
CAS: 22464-99-9 EINECS: 245-018-1 Reg.nr.: 01-2119979088-21	2-ethylhexanoic acid, zirconium salt Repr. 2, H361d; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<1%
CAS: 85-44-9 EINECS: 201-607-5 Reg.nr.: 01-2119457017-41	phthalic anhydride Resp. Sens. 1, H334; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT	<1%

SE 3, H335

**Additional information:** For the wording of the listed hazard phrases, refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General information:** Immediately remove any clothing soiled by the product.
- After inhalation:** Supply fresh air; consult doctor in case of complaints.
- After skin contact:** Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Immediately rinse with water.
- After eye contact:** Rinse opened eye for several minutes under running water.
- After swallowing:** Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents:** Water with full jet

### 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

### 5.3 Advice for firefighters

**Protective equipment:** Mount respiratory protective device.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.

### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.  
 Prevent seepage into sewage system, workpits and cellars.  
 Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.

### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Dispose contaminated material as waste according to item 13.  
 Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Keep receptacles tightly sealed.
- Ensure good ventilation/extraction at the workplace.
- Prevent formation of aerosols.
- Hygiene measures:
- Wash hands before breaks and at the end of workday.

<b>Information about fire – and explosion protection:</b>	Keep ignition sources away – Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
---	---

### 7.2 Conditions for safe storage, including any incompatibilities

<b>Requirements to be met by storerooms and receptacles:</b>	Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product, may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside
<b>Information about storage in one common storage facility:</b>	Not required.
<b>Further information about storage conditions:</b>	Keep receptacle tightly sealed and in a well-ventilated place. Keep away from heat.

### 7.3 Specific end use(s)

No further relevant information available.

## SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

### 8.1 Control parameters

<b>Ingredients with limit values that require monitoring at the workplace:</b>		
<b>Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>		
OEL	Short-term value: 1200 mg/m <sup>3</sup>	
<b>Solvent naphtha (petroleum), light aromatic</b>		
OEL	Long-term value: 100 mg/m <sup>3</sup>	
<b>1330-20-7 Xylene (mix)</b>		
WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV	
<b>96-29-7 2-butanone oxime</b>		
OEL	Long-term value: 1 mg/m <sup>3</sup> , 0.3 ppm	
<b>136-52-7 cobalt bis(2-ethylhexanoate)</b>		
WEL	Long-term value: 0.1 mg/m <sup>3</sup> as Co; Carc, Sen	
<b>85-44-9 phthalic anhydride</b>		
WEL	Short-term value: 12 mg/m <sup>3</sup> Long-term value: 4 mg/m <sup>3</sup> Sen	
<b>DNELs</b>		
<b>Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)</b>		
Oral	DNEL	26 mg/day (Con)
Dermal	DNEL	26 mg/day (Con)
Inhalative	DNEL	44 mg/day (Ind)
		71 mg/m <sup>3</sup> (Con)
		330 mg/m <sup>3</sup> (Ind)
<b>Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>		
Oral	DNEL	125 mg/day (Con)
Dermal	DNEL	125 mg/day (Con)
Inhalative	DNEL	208 mg/day (Ind)
		185 mg/m <sup>3</sup> (Con)
		871 mg/m <sup>3</sup> (Ind)
<b>Solvent naphtha (petroleum), light aromatic</b>		
Oral	DNEL	11 mg/day (Con)
Dermal	DNEL	11 mg/day (Con)
Inhalative	DNEL	25 mg/day (Ind)
		32 mg/m <sup>3</sup> (Con)
		150 mg/m <sup>3</sup> (Ind)
<b>138-86-3 4-isopropenyl-1-methylcyclohexane</b>		
Oral	DNEL	4.76 mg/day (Con)
Dermal	DNEL	111 mg/day (Con)
Inhalative	DNEL	222 mg/day (Ind)
		8.33 mg/m <sup>3</sup> (Con)
		33.3 mg/m <sup>3</sup> (Ind)
<b>1330-20-7 Xylene (mix)</b>		
Dermal	DNEL	108 mg/day (Con)
Inhalative	DNEL	180 mg/day (Ind)
		14.8 mg/m <sup>3</sup> (Con)
		77 mg/m <sup>3</sup> (Ind)
<b>96-29-7 2-butanone oxime</b>		
Dermal	DNEL	0.78 mg/day (Con)

Inhalative	DNEL	1.3 mg/day (Ind) 2.7 mg/m <sup>3</sup> (Con) 9 mg/m <sup>3</sup> (Ind)
------------	------	--

<b>PNECs</b>	
<b>CAS No. 1330-20-7 Xylene mixed isomers</b>	
- Fresh water; 0.327 mg/l - Marine water; 0.327 mg/l - Intermittent release; 0.327 mg/l - STP; 6.58 mg/l - Sediment (Freshwater); 12.46 mg/kg - Sediment (Marine water); 12.46 mg/kg - Soil; 2.31 mg/kg	

<b>Ingredients with biological limit values:</b>	
<b>1330-20-7 Xylene (mix)</b>	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

**Additional information: The lists valid during the making were used as basis.**

## 8.2 Exposure controls

### Personal protective equipment:

#### • General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

#### • Respiratory protection:

When spraying the product, use a respiratory protective device.

#### • Protection of hands:

When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



### Protective Gloves

#### • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

#### • Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### • Eye protection:



### Tightly Sealed Goggles

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

<b>Appearance</b>	
Form:	Liquid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
<b>Change in condition</b>	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	139 °C
Flash point:	>29 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>230 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not self-igniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Explosion limits</b>	
Lower:	0.6 Vol %
Upper:	7 Vol %
Vapour pressure at 20 °C:	2 hPa
Density at 20 °C:	0.908 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	NOT MISCIBLE
Partition coefficient: n-octanol/water:	Not determined.
<b>Viscosity</b>	
Dynamic at 20 °C:	320 mPas
Kinematic:	Not determined.
<b>Solvent content</b>	
Organic solvents:	55.4 %
Water:	0.0 %
Solids content:	44.5 %

### 9.2 Other information

No further relevant information available.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity</b>	No further relevant information available.
<b>10.2 Chemical stability</b>	Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
<b>10.3 Possibility of hazardous reactions</b>	No dangerous reactions known.
<b>10.4 Conditions to avoid</b>	No further relevant information available.
<b>10.5 Incompatible materials:</b>	No further relevant information available.

**10.6 Hazardous decomposition products** No dangerous decomposition products when stored and handled correctly

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**Acute toxicity**

Based on available data, the classification criteria are not met.

<b>LD/LC50 values relevant for classification:</b>		
<b>Hydrocarbons, C9 -12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)</b>		
Oral	LD50	>15,000 mg/kg (Rat)
Dermal	LD50	>3,400 mg/kg (Rab)
Inhalative	LD50/4h	13.1 mg/l (Rat)
<b>Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>		
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rat)
<b>Solvent naphtha (petroleum), light aromatic</b>		
Oral	LD50	3,492 mg/kg (Rat)
Dermal	LD50	3,160 mg/kg (Rab)
Inhalative	LC50/4 h	>6.193 mg/l (Rat)
<b>138-86-3 4-isopropenyl-1-methylcyclohexane</b>		
Oral	LD50	>2,000 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rab)
<b>1330-20-7 Xylene (mix)</b>		
Oral	LD50	5,000 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (Rab)
Inhalative	LC50/4 h	11 mg/l (Rat)
<b>96-29-7 2-butanone oxime</b>		
Oral	LD50	2,326 mg/kg (rat)
Dermal	LD50	1,000 mg/kg (Rab)
Inhalative	LD50/4h	200-2,000 mg/kg (rat)
		>4.8 mg/l (rat)

**Primary irritant effect:**

**Skin corrosion/irritation:** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation:** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation:** Based on available data, the classification criteria are not met.

**CMR effects**

**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

**Carcinogenicity:** Based on available data, the classification criteria are not met.

**Reproductive toxicity:** Based on available data, the classification criteria are not met.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure** Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Acute Fish toxicity:

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)  
 LC50 9.22 mg/l  
 Species: Oncorhynchus mykiss (rainbow trout)  
 Exposure duration: 96 h

#### Acute toxicity for daphnia

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)  
 EC50 6.14 mg/l  
 Species: Daphnia magna (Water flea)  
 Exposure duration: 48 h

#### Acute toxicity for algae

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)  
 ErC50 2.9 mg/l  
 Species: Pseudokirchneriella subcapitata (green algae)  
 Exposure duration: 72 h

#### Acute bacterial toxicity

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)  
 EC50 1 - 10 mg/l

#### Ecotoxicology Assessment

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)  
 Chronic aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Data based on the safety data sheet (SDS) by the supplier.

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

#### Ecotoxicological effects:

- Remark: Toxic for fish
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
 Do not allow product to reach ground water, water course or sewage system.  
 Danger to drinking water if even small quantities leak into the ground.  
 Also poisonous for fish and plankton in water bodies.  
 Toxic for aquatic organisms

**12.5 Results of PBT and vPvB assessment** PBT: Not applicable.  
 vPvB: Not applicable.

**12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

<b>Recommendation</b>	Must not be disposed together with household garbage. Do not allow product to reach sewage system.
<b>Uncleaned packaging:</b>	Disposal must be made according to official regulations.

**SECTION 14: Transport information**

**14.1 UN-Number**

ADR, IMDG, IATA UN1263

**14.2 UN proper shipping name**

ADR 1263 PAINT RELATED MATERIAL, ENVIRONMENTALLY HAZARDOUS  
IMDG PAINT RELATED MATERIAL (TURPENTINE SUBSTITUTE, DIPENTENE), MARINE POLLUTANT  
IATA PAINT RELATED MATERIAL

**14.3 Transport hazard class(es)**

IATA   
Class 3 Flammable Liquids  
Label 3

ADR, IMDG    
Class 3 Flammable Liquids  
Label 3

**14.4 Packing group**

ADR, IMDG, IATA III

**14.5 Environmental hazards**

Environmental hazards: Product contains environmentally hazardous substances: 4-isopropenyl-1-methylcyclohexane  
Marine pollutant: Symbol (fish and tree)  
Special marking (ADR): Symbol (fish and tree)

**14.6 Special precautions for user**

Special Precautions: Warning: Flammable liquids.  
Hazard ID number (Kemler code): 30  
EMS Number: F-E,S-E  
Stowage Category: A

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

**Transport/Additional information:**

**ADR**  
Limited quantities (LQ) 5L  
Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml  
Transport category 3  
Tunnel restriction code D/E

**IMDG**  
Limited quantities (LQ) 5L  
Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation" UN 1263 PAINT RELATED MATERIAL, 3, III, ENVIRONMENTALLY HAZARDOUS

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

<b>DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II</b>
---

None of the ingredients is listed.
------------------------------------

National regulations:

Technical instructions (air):

Class	Share in %
I	0.3
NK	2.9

Waterhazard class: Water danger class 1 (Self-assessment): slightly hazardous for water.

### 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Full text of H-Statements referred to under sections 2 and 3:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360F	May damage fertility.
H361d	Suspected of damaging the unborn child.

H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

<b>Acute Tox. 4</b>	Acute toxicity - dermal - Category 4
<b>ADR</b>	Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment - acute aquatic hazard - Category 1
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment - long-term aquatic hazard - Category 3
<b>Asp. Tox. 1</b>	Aspiration hazard - Category 1
<b>Carc. 2</b>	Carcinogenicity - Category 2
<b>CAS</b>	Chemical Abstracts Service (division of the American Chemical Society)
<b>DNEL</b>	Derived No-Effect Level (REACH)
<b>EINECS</b>	European Inventory of Existing Commercial Chemical Substances
<b>ELINCS</b>	European List of Notified Chemical Substances
<b>Eye Dam. 1</b>	Serious eye damage/eye irritation - Category 1
<b>Eye Irrit. 2</b>	Serious eye damage/eye irritation - Category 2
<b>Flam. Liq. 3</b>	Flammable liquids - Category 3
<b>GHS</b>	Globally Harmonised System of Classification and Labelling of Chemicals
<b>IATA</b>	International Air Transport Association
<b>ICAO:</b>	International Civil Aviation Organisation
<b>IMDG</b>	International Maritime Code for Dangerous Goods
<b>LC50</b>	Lethal concentration, 50 percent
<b>LD50</b>	Lethal dose, 50 percent
<b>PBT</b>	Persistent, Bioaccumulative and Toxic
<b>PNEC</b>	Predicted No-Effect Concentration (REACH)
<b>Repr. 1B</b>	Reproductive toxicity - Category 1B
<b>Repr. 2</b>	Reproductive toxicity - Category 2
<b>RID:</b>	Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
<b>Skin Irrit. 2</b>	Skin corrosion/irritation - Category 2
<b>Skin Sens. 1</b>	Skin sensitisation - Category 1
<b>STOT RE 1</b>	Specific target organ toxicity (repeated exposure) - Category 1
<b>STOT SE 3</b>	Specific target organ toxicity (single exposure) - Category 3
<b>vPvB</b>	very Persistent and very Bioaccumulative