



Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.bondaglass.com

June 2018

PRODUCT DATA SHEET

Product	Bonda Wood Stop – Wood & Grain Filler
Type	Air dried one-part wood filler.
Intended Use	For small holes, splits and damaged areas on the surface of hard or soft woods. For interior and exterior use.
Special Features	Perfect for filling surface imperfections and damaged wood grain.
Preparation	Should be applied onto a clean and dry substrate.
Application	Apply using a putty knife, forcing into the cracks and holes. Leave slightly proud of the surface to allow for possible shrinkage and to enable sanding. Allow to dry for 2 hours under good conditions. Never exceed layers of 3 mm when applying or shorten the drying time. If it is cold or damp it may require longer to dry. If the hole to be filled is deep, it should be filled in layers of 3 mm allowing each to dry before further layers are applied.
Coats	Non-applicable.
Curing Time	2 hours depending on the temperature and humidity. Do not use below 10°C or in high humidity.
Re-coating Time	Leave to dry for 2-3 hours before applying undercoat or varnish. Deep filled area may require longer.
Application Temp.	Ideally 15-25°C, but do not use below 10°C.
Coverage	Non-applicable.
Maintenance	Not applicable.
Compatibility	Can be used under all Rustins paints and varnishes. Most other brands should be compatible but if in doubt carry out a small test. Always test first on an inconspicuous area to check that the colour is correct. The Wood Filler may accept dyes and stains differently to the surrounding wood.
Settlement	Stir well if there is any sign of separation.
Shelf-life/Storage	A very long time if stored in original sealed container in a cool dry place. Do not store below 5°C.
Hazards	Keep out of reach of children. Wash hands after use. A Safety Data Sheet is available upon request or from www.bondaglass.com
Clean-Up	Clean all equipment immediately after use with warm water.
Sizes	250ml