

MATERIAL SAFETY DATA SHEET

UNDERCOAT (ALL COLOURS)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier For Industrial, professional and consumer only

Trade name: Symphony Narrowboat Paint Undercoat (All Colours)

1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating

Relevant uses: Surface Coating

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet

Supplier: SYMPHONY COATINGS GROUP LTD
10A GRANGE WAY
WHITEHALL IND EST
COLCHESTER
CO2 8HG
UNITED KINGDOM
Tel: +44 (0)1206 868400
Email: hs@symphonynarrowboatpaint.co.uk

Further information from: hello@symphonynarrowboatpaint.co.uk

1.4 Emergency number +44 (0)1206 868400 (business hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour
STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:



Signal word: Danger

Hazard-determining components of labelling: Contains 4-isopropenyl-1-methylcyclohexane
2-butanone oxime
May produce an allergic reaction

Hazard statements: H226 Flammable liquid and vapour
H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards






Results of PBT and vPvB assessment: PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.1 Substance: Non-applicable

3.2 Mixture: Mixture of substances listed below with non-hazardous additions.

Dangerous components:

EC number: 919-446-0 Reg.nr.: 01-2119458049-33-xxxx	Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 	10-25%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 	2.5-10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate 	<2.5%
CAS: 138-86-3 EINECS: 205-341-0 Reg.nr.: 01-2120766421-57-0000	4-isopropenyl-1-methylcyclohexane 	<2.5%
CAS: 96-29-7 EINECS: 202-496-6 Reg.nr.: 01-2119539477-28	2-butanone oxime 	<2.5%

Additional information: For the wording of the listed hazard phrases, refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Immediately rinse with water.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Keep receptacles tightly sealed.
- Ensure good ventilation/extraction at the workplace.
- Prevent formation of aerosols.
- Hygiene measures:
- Wash hands before breaks and at the end of workday.

Information about fire - and explosion protection:	Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
---	---

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:	Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product, may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside
Information about storage in one common storage facility:	Not required.
Further information about storage conditions:	Keep receptacle tightly sealed and in a well-ventilated place. Keep away from heat.

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:		
108-65-6 2-methoxy-1-methylethyl acetate		
WEL		Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
DNELs		
Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
Oral	DNEL	26 mg/day (Con)
Dermal	DNEL	26 mg/day (Con)
		44 mg/day (Ind)
Inhalative	DNEL	71 mg/m ³ (Con)
		330 mg/m ³ (Ind)

**Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics,
<2% aromatics**

Oral	DNEL	125 mg/day (Con)
Dermal	DNEL	125 mg/day (Con) 208 mg/day (Ind)
Inhalative	DNEL	185 mg/m ³ (Con) 871 mg/m ³ (Ind)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	DNEL	1.67 mg/day (Con)
Dermal	DNEL	54.8 mg/day (Con) 153 mg/day (Ind)
Inhalative	DNEL	33 mg/m ³ (Con) 275 mg/m ³ (Ind)

138-86-3 4-isopropenyl-1-methylcyclohexane

Oral	DNEL	4.76 mg/day (Con)
Dermal	DNEL	111 mg/day (Con) 222 mg/day (Ind)
Inhalative	DNEL	8.33 mg/m ³ (Con) 33.3 mg/m ³ (Ind)

96-29-7 2-butanone oxime

Dermal	DNEL	0.78 mg/day (Con) 1.3 mg/day (Ind)
Inhalative	DNEL	2.7 mg/m ³ (Con) 9 mg/m ³ (Ind)

PNECs

CAS No. 1330-20-7 Xylene mixed isomers

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marine water); 12.46 mg/kg
- Soil; 2.31 mg/kg

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

• Respiratory protection:

When spraying the product, use a respiratory protective device.

• Protection of hands:

When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective Gloves

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

• Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly Sealed Goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

<u>Appearance</u>	
Form:	Liquid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
<u>Change in condition</u>	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	135 °C
Flash point:	>30 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not self-igniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<u>Explosion limits</u>	
Lower:	0.6 Vol %
Upper:	7 Vol %
Vapour pressure at 20 °C:	Not determined
Density at 20 °C:	1.262 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	NOT MISCIBLE
Partition coefficient: n-octanol/water:	Not determined.
<u>Viscosity</u>	
Dynamic at 20 °C:	200 mPas
Kinematic:	Not determined.
<u>Solvent content</u>	
Organic solvents:	2.97 %
Water:	0.0 %
Solids content:	67.9 %

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity	No further relevant information available.
10.2 Chemical stability	Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
10.3 Possibility of hazardous reactions	No dangerous reactions known.
10.4 Conditions to avoid	No further relevant information available.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition products	No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
Oral	LD50	>15,000 mg/kg (Rat)
Dermal	LD50	>3,400 mg/kg (Rab)
Inhalative	LD50/4h	13.1 mg/l (Rat)
Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rat)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	5,000 mg/kg (Rat)
Inhalative	LC50/4 h	>10.8 mg/l (Rat)
138-86-3 4-isopropenyl-1-methylcyclohexane		
Oral	LD50	>2,000 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rab)
96-29-7 2-butanone oxime		
Oral	LD50	2,326 mg/kg (rat)
Dermal	LD50	1,000 mg/kg (Rab)
Inhalative	LD50/4h	200-2,000 mg/kg (rat)
		>4.8 mg/l (rat)

Primary irritant effect:	
Skin corrosion/irritation:	Based on available data, the classification criteria are not met.
Serious eye damage/irritation:	Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation:	Based on available data, the classification criteria are not met.
CMR effects	
Germ cell mutagenicity:	Based on available data, the classification criteria are not met.
Carcinogenicity:	Based on available data, the classification criteria are not met.
Reproductive toxicity:	Based on available data, the classification criteria are not met.
STOT- single exposure	Based on available data, the classification criteria are not met.
STOT- repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Based on available data, the classification criteria are not met.

SECTION 12: Ecological information


12.1 Toxicity	Aquatic toxicity: No further relevant information available.
12.2 Persistence and degradability	No further relevant information available.
12.3 Bioaccumulative potential	No further relevant information available.
12.4 Mobility in soil	No further relevant information available.
Ecotoxicological effects: - Remark: Toxic for fish - Additional ecological information: - General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Harmful to aquatic organisms	
12.5 Results of PBT and vPvB assessment	PBT: Not applicable. vPvB: Not applicable.
12.6 Other adverse effects	No further relevant information available.



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation	Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Uncleaned packaging:	Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR IMDG IATA	1263 PAINT RELATED MATERIAL, ENVIRONMENTALLY HAZARDOUS PAINT RELATED MATERIAL (TURPENTINE SUBSTITUTE, DIPENTENE), MARINE POLLUTANT PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
ADR	
Class	3 Flammable Liquids
Label	3

IMDG	 
Class Label	3 Flammable Liquids 3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards	
Environmental hazards:	Product contains environmentally hazardous substances: 4-isopropenyl-1-methylcyclohexane
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	
Special Precautions:	Warning: Flammable liquids.
Hazard ID number (Kemler code):	30
EMS Number:	F-E,S-E
Stowage Category:	A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	
Not applicable.	
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation"	UN 1263 PAINT RELATED MATERIAL, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU
 Named dangerous substances - ANNEX I None of the ingredients is listed.
 Seveso category
 E2 Hazardous to the Aquatic Environment
 P5c FLAMMABLE LIQUIDS
 Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
 Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
 REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:

Technical instructions (air):

Class	Share in %
I	0.3
NK	2.9

Waterhazard class: Water danger class 1 (Self-assessment): slightly hazardous for water.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Full text of H-Statements referred to under sections 2 and 3:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

Acute Tox. 4	Acute toxicity - dermal - Category 4
ADR	Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute 1	Hazardous to the aquatic environment - acute aquatic hazard - Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - long-term aquatic hazard - Category 3
Asp. Tox. 1	Aspiration hazard - Category 1
Carc. 2	Carcinogenicity - Category 2
CAS	Chemical Abstracts Service (division of the American Chemical Society)
DNEL	Derived No-Effect Level (REACH)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
Eye Dam. 1	Serious eye damage/eye irritation - Category 1
Eye Irrit. 2	Serious eye damage/eye irritation - Category 2
Flam. Liq. 3	Flammable liquids - Category 3
GHS	Globally Harmonised System of Classification and Labelling of Chemicals
IATA	International Air Transport Association

ICAO:	International Civil Aviation Organisation
IMDG	International Maritime Code for Dangerous Goods
LC50	Lethal concentration, 50 percent
LD50	Lethal dose, 50 percent
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No -Effect Concentration (REACH)
Repr. 1B	Reproductive toxicity – Category 1B
Repr. 2	Reproductive toxicity – Category 2
RID:	Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
Skin Irrit. 2	Skin corrosion/irritation – Category 2
Skin Sens. 1	Skin sensitisation – Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) – Category 1
STOT SE 3	Specific target organ toxicity (single exposure) – Category 3
vPvB	very Persistent and very Bioaccumulative